

# HOT BOX 200/500 Heater Modules

Many companies facing cleaning problems usually solve them with cold water high pressure cleaners. There are, however, many kinds of contamination which can be removed more effectively with hp hot water.

With heater module HOT BOX 200/500 OERTZEN offers a most capable and effective accessory for changing a cold water hp cleaner into a hot water one.

In order to start hot water hp cleaning, HOT BOX module is simply installed between high pressure cleaner and spraying device.

HOT BOX is a hot water generator with vertical burner (fuel oil operated) which heats up a coil with hp water passing through (pressure range 170 - 500 bar). For trouble-free, safe operating at heavy workload, HOT BOX has significant safety and control features:

- safety valve protects module against overpressure
- exhaust thermostat protects module against overheating
- flow switch controls feeding rate
- thermostat controls adjusted temperature.



Pic. shows  
HOT BOX 200 coupled to 312 Profi hp cleaner

Technical data	HOT BOX 200	HOT BOX 500
Feeding rate	540-1380 l/h	540-1380 l/h
Unloading pressure	270 bar	520 bar
Working pressure max.	250 bar	500 bar
Water temperature (adjustable)	50-130 °C	50-130 °C
Heating capacity	59000 kcal/h	75000 kcal/h
Standard voltage	230V/1~50 Hz	230V/1~50 Hz
Dimensions (LxWxH mm - length incl. fuel tank 800 mm)	630 x 640 x 950	630 x 640 x 1010
Weight	79 kg	109 kg
Order No.	10.000.092	10.000.094

**Serial equipment:** fuel oil tank 20 l (jerry can), 2 m PANZERJET high pressure connection hose, 4 m power cable with european plug